

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
19 May 2005 (19.05.2005)

PCT

(10) International Publication Number
WO 2005/045376 A1

(51) International Patent Classification⁷: **G01H 3/10**

(21) International Application Number:
PCT/DK2004/000778

(22) International Filing Date:
10 November 2004 (10.11.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PA 2003 01666 10 November 2003 (10.11.2003) DK

(71) Applicant (for all designated States except US): **BRÜEL & KJÆR** [DK/DK]; Sound & Vibration Measurement A/S, Skodsborgvej 307, 2850 Nærum (DK).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **HALD, Jørgen** [DK/DK]; Overblikket 8, DK-3460 Birkerød (DK).

(74) Agent: **ZACCO DENMARK A/S**; Hans Bekkevolds Allé 7, DK-2900 Hellerup (DK).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A METHOD OF DETERMINING THE SOUND PRESSURE RESULTING FROM A SURFACE ELEMENT OF A SOUND EMITTING SURFACE



(57) Abstract: A three-dimensional array (10) of microphones (M) is used to determine the three-dimensional sound field above a surface element (ΔS) of a sound emitting surface (S), and the air-particle velocity (u_n) at the surface element (ΔS) is determined using Near-Field Acoustical Holography (NAH). A volume velocity sound source (11) is used to emit a volume velocity (Q_v) in a listening position, and the array (10) of microphones (M) is used to determine the resulting three-dimensional sound field above the surface element (ΔS), and using NAH the resulting sound pressure at the surface element (ΔS) is determined. The acoustic transfer function (H) between the surface element (ΔS) and the listening position is assumed to be reciprocal and is determined as the ratio of the resulting sound pressure at the surface element (ΔS) to the volume velocity (Q_v). The sound pressure in the listening position resulting from the surface element (ΔS) is determined as $\Delta p = H \cdot (u_n \cdot \Delta S)$.

WO 2005/045376 A1